



## EASY SETUP

The DM-100 is ready to function as soon as you connect it to a power source. With all necessary tools and components included, assembly is quick and operator training is minimized. When connected to a network via DHCP or static IP, the embedded firmware provides access to additional screens and configuration parameters - no additional software installation is required.

## INNOVATIVE TECHNOLOGY

DM-100's multiple patented, innovative sensing technology and 3D imaging work together to optimize time and throughput for boxes, flats, polybags, tubes and irregular-shaped packages. For flats or packages under 1.2 inches, use the flat detection trigger located on the base plate or connect to a compatible scale.

## OPERATOR DISPLAY

With the standard operator display already attached to the frame, setup is easy and operation is simple. DM-100 provides length, width and height. Integrating an existing compatible scale adds weight to the displayed data.

## OPERATING VERSATILITY

Use the standard automatic operating mode to instantly scan a parcel when it is placed in the target zone. Improve process time and efficiency with virtually no special alignment or special handling.

## SPEED AND ACCURACY

Parcels are dimensioned more accurately and faster than manual measurements, eliminating the risk of human error. In an industry leading 0.2 seconds, NTEP Certified dimensions are calculated within 0.2 inches of accuracy. Irregular-shaped packages like cylinders, spheres, tubes, polybags and uneven shapes are dimensioned within an NTEP Certified 0.5 inches of accuracy.

## ADVANCED DATA MANAGEMENT

As a network device, take advantage of the simple, open-web service API to interface to third-party software programs and capture dimensions, weight and an image of the item. Create your own program and trigger the DM-100 to dimension an item and store data of each shipment or receipt of product.

## SHIPPING & WAREHOUSE MANAGEMENT SOFTWARE COMPATIBILITY

Contact Sasco Africa for an up-to-date listing of compatible software programs.

**Industry Leading 0.2  
Second Dimensioning**



## STANDARD FEATURES

- Calculates NTEP Certified dimensions in 0.2 seconds
- Displays dimensions, weight and image of static items with included USB operator display
- No moving parts, no special handling
- Quick assembly—including all necessary hardware and tools
- No PC interface required to set up, configure or manually enter dimensions into third-party software
- Optional PC connection available with provided Ethernet cable. Communicate directly over a network via static IP or DHCP
- Interfaces with most NTEP Certified shipping scales and select Rice Lake Weighing Systems indicators via USB connection

## SPECIFICATIONS

PHYSICAL	
Dimensions:	Length: 64 cm
	Width: 56 cm
	Height: 162 cm
	Weight: 13 kg
Power:	Single power source 110-240 V external power supply
COMPATIBLE	
Colors:	All opaque packaging; some variances may occur with glossy surfaces or shrink wrap
Measurement Surfaces:	Level tables, scales, roller balls and roller conveyors. The background should have a contrasting color for items to be dimensioned. Avoid over-polished or glossy surfaces like stainless steel weight platters and flat black paint for best performance.
OPERATING	
Temperature:	41° F to 104° F (5° C to 40° C)
Humidity:	Non-condensing
Mechanical Environment Class:	M1
Electromagnetic Class:	E1
I/O Ports:	(1) USB type A port (interface to scale)
	(1) 10/100/100BASE-T Ethernet port (Interface to PC)
Package Contents:	DM-100 assembly tools, calibration object, USB display and U.S. power cord
Warranty:	One-year limited warranty





## NTEP CERTIFIED MEASUREMENT RANGES

Measurement	Min. (in)	Max. (in)	Division
<b>CUBE</b>			
Length	5.6	48	0.2
Width	5.6	28	0.2
Height	2.4	28	0.2
<b>IRREGULAR</b>			
Length	6	48	0.5
Width	6	28	0.5
Height	5	28	0.5

## OIML CERTIFIED MEASUREMENT RANGE

Measurement	Min. (in)	Max. (in)	Division
Length	12	80	0.5
Width	10	60	0.5
Height	5	70	0.5
<b>OR</b>			
Length	12	120	0.5
Width	10	75	0.5
Height	5	30	0.5

**Note:** Minimum and maximum certified capabilities do not reflect non-certified performance specifications.  
Contact Sasco Africa for more assistance

### SMART SUPPORT

**0861 422 134 OR +27 83 680 0722**

E-mail: [info@sascoafrica.com](mailto:info@sascoafrica.com)

Web: [www.sascoafrica.com](http://www.sascoafrica.com)

24 hours, 7 Days a week

### Group Support Head Office:

2 Blackburn Street  
Apex Industrial  
Benoni

Phone: +27 (0) 11 746 6000

Fax: +27 (0) 11 746 6100

This brochure contains a general guide of the product only and shall not form part of any contract unless specifically agreed by Sasco Africa in writing in each case on the Order Acknowledgement. The specification of the product described herein may vary from time to time and may be altered without notice. Sasco Africa, its directors, staff, owners and affiliated companies and organisations cannot be held liable for any resulting damage or injury sustained as a result of the machines being used in excess of their capacities and ultimate overload limits.

